N 90, Built-in oven with added steam function, 60 x 60 cm, Graphite-Grey

B64VS71G0B







Z11AB15A0 Baking tray, non-stick ceramic coated Z11CR10X0 Baking and roasting grid (standard) Z11SZ00X0 SeamlessCombination mounting kit Z11SZ80G0 SeamlessCombination 60 + 29cm Z11SZ90G0 SeamlessCombination 60 + 45cm Z12CB10A0 Baking tray, anthracite enamelled Z12CM10A0 Moussaka pan, anthracite enamelled

Z13CV06S0 Decor strip

Z1608CX0 Full ext rails, level independent, pyro

Z1650BE0 Half trav

Z1655CA0 Air Fry & Grill tray, anthracite

Built-in oven Vario Steam with Slide & Hide® - an easy to handle door that gently disappears under the oven. Home Connect control your oven via the App.

- $\sqrt{4,1}$ " Full Touch TFT Display Easy to use and intuitive menu for smart and enjoyable cooking.
- $\sqrt{\,}$ Slide & Hide $^{\tiny @}$ An easy to handle door that disappears under the oven for unrestricted access.
- $\sqrt{\,}$ Vario Steam For food that's moist on the inside and crisp on the
- $\sqrt{\,}$ Steam Boost Fill your oven with steam quickly for ultimate flavour and texture.
- √ Circo Therm® our smart hot-air solution for simultaneous baking and roasting on up to four levels

Technical Data

Color / Material Front : Graphite Construction type: Built-in

Integrated Cleaning system : Pyrolytic+Hydrolytic

Min. required niche size for installation (HxWxD): 585-595 x 560-568

Dimensions: 595 x 596 x 548 mm

Dimensions of the packed product (HxWxD) : $660 \times 690 \times 650$ mm

Control Panel Material: Stainless steel

Door Material: Glass Net weight: 44.9 kg Usable volume of cavity: 71 |

Cooking method: 4D Hotair, Bottom heat, Bread Baking Setting, Conventional heat, Conventional heat gentle, Full width grill, Half width grill, Hotair gentle, Hot air grilling, low temperature cooking,

Pizza setting, pre-heating, Regeneration, warming

Oven control: electronic Number of interior lights: 1

Length of electrical supply cord: 120.0 cm

EAN code: 4242004266198 Number of cavities (2010/30/EC): 1

Energy efficiency rating: A+

Energy consumption per cycle conventional (2010/30/EC): 0.87

kWh/cvcle

Energy consumption per cycle forced air convection (2010/30/EC) :

0.69 kWh/cycle

Energy efficiency index (2010/30/EC): 81.2 %

Connection rating: 3600 W Fuse protection: 16 A Voltage: 220-240 V Frequency: 50; 60 Hz

Plug type: no plug (electrical connection by electrician) Included accessories: 2 x combination grid, 1 x universal pan





N 90, Built-in oven with added steam function, 60 x 60 cm, Graphite-Grey B64VS71G0B

Features

 Oven with 20 heating methods: CircoTherm®, Top/bottom heat, Circo-roasting, Full surface grill, Centre surface grill, CircoTherm® intensive, Bread baking, Bottom heat, Low temperature cooking, Plate warming, Keep warm, CircoTherm® gentle, Conventional heat gentle, Reheat with steam, Dough proving, Circo-roasting, Bread Baking Setting, warming, 4D Hot air, Top/bottom heat

Design

- Graphite-Grey Edition
- Touch control
- Cavity inner surface: enamel anthracite

Features

- HomeConnect ready on WLAN
- Oven Assistant with Voice Control
- Door lock during pyrolytic cleaning Control panel lock Automatic safety switch off Residual heat indicator Start button Door contact switch
- Full glass inner door

Programmes/functions

- Temperature range 40 °C 200 °C
- LED light, On/off button
- Electronic clock timer
- Slide&Hide® with rotating handle
- Water tank empty indicator
- Location of water tank: Outside cavity
- SoftClose, SoftOpen
- Quadruple glazed door glazed CoolTouch door
- 30 °C Very low door temperature
- Temperature proposal Actual temperature display Heating up indicator
- cookControl Plus
- Rapid heat
- steam boost add for 3min intensive steam with a touch of a button.
- There are different steam intensities selectable: steam level high, steam level middle, steam level low
- Cooling fan
- Stainless-steel fan

Level independent telescopic rails

- 4 shelf positions
- Available as an accessory, pyrolytic proof

Cleaning

- Pyrolytic cleaning
- EasyClean

Accessories

• 2 x combination grid, 1 x universal pan

Performance/technical information

- 120 cm Cable length
- Nominal voltage: 220 240 V
- Total connected load electric: 3.6 KW
- Energy efficiency rating (acc. EU Nr. 65/2014): A+ Energy consumption per cycle in conventional mode:0.87 kWh Energy consumption per cycle in fan-forced convection mode:0.69 kWh

Number of cavities: Main cavity Heat source: electrical Cavity volume:71 litre


- Appliance dimension (hxwxd): 595 mm x 596 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual



N 90, Built-in oven with added steam function, 60 x 60 cm, Graphite-Grey B64VS71G0B


COOKING PASSION SINCE 1877


Dimensioned drawings





If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm









A: Air inlet ≥ 200 cm²